



Surface Mount Lifts

FOR ALL OF TODAY'S VEHICLES... AND TOMORROW'S

Two Post Lifts

10,000 lb Capacity

- Choice of symmetric or asymmetric columns.
- Direct pull lifting with closed-loop hydraulic system.
- Dual safety release system.
- Powder-coated finish.
- Features low-profile arms - 3¼"

	2A10	2S10	2A10X	2S10X
Capacity	10,000 LBS.	10,000 LBS.	10,000 LBS.	10,000 LBS.
Overall Height	11' 11½"	11' 11½"	13' 11½"	13' 11½"
Height to Shut Off	11' 4"	11' 4"	13' 4"	13' 4"
Min. Ceiling Height	12'	12'	14'	14'
Min. Lifting Height	3¾"	3¾"	3¾"	3¾"
Max. Lifting Height	77"	77"	77"	77"
Overall Floor Width	11' 5"	11' 5"	11' 5"	11' 5"
Inside Column Width	115¾"	115¾"	115¾"	115¾"
Drive Through	95"	104"	95"	104"
Voltage	208/230	208/230	208/230	208/230
Amps	20	20	20	20
Motor	2HP	2HP	2HP	2HP
Asymmetric	Yes	No	Yes	No
Symmetric	No	Yes	No	Yes



Two Post Optional Accessories

- FD070606 Screw Type Adapter Kit, Set of 4 with Rubber Pads and Hardware
- FD070607 Slip On 6" Truck Type Extensions, Set of 4 with Rubber Pads and Hardware
- FD106605 DP Stack Pad Weldment, Set of 4 with Rubber Pads and Hardware
- FD994105 Rubber Pad Inserts, Set of 4 with Hardware
- FD995550 6" Stack Pad Adapters
- FD995560 3" Stack Pad Adapters
- FD996220 1.5" Stack Pad Adapters

Brake and Tire Speciality Lift TL10000

- Designed for quick brake and tire service.
- Compact size is perfect for smaller service bays.



Length	90½"
Width	84½"
Full Rise	305½" with Adapters
Fully Lowered	4"
Weight Capacity	10,000 LBS.
Shipping Weight	1,200 LBS.
Portable	No
Voltage	115 VAC

Mid-Rise Scissor Lift MR6000

- Portable mid-rise lift is ideal for busy shops with limited space.



Length	83"
Width	41"
Full Rise	52"
Fully Lowered	5"
Weight Capacity	6,000 LBS.
Shipping Weight	1,000 LBS.
Portable	Yes
Voltage	115 VAC

Alignment Four Post Lifts

12,000 lb Capacity Open Front

Models 4A12 and 4A12X

- Standard features include rear wheel slip plates and front work step.
- Optional package available, includes two RJ6 Rolling Air Jacks (4A12PKG or 4A12XPKG).



General Service Four Post Lift

14,000 lb Capacity Closed Front

Models 4S14C and 4S14CX

- Heavy-duty hydraulic cylinder.
- Single point safety release system.
- Slack chain safety feature in each structural leg.
- Optional package available (4S14CPKG) includes two RJ6 Rolling Air Jacks.

Four Post Optional Accessories

RJ6	Rolling Jack - 6,000 lbs capacity
FD991552	Internal Airline Kit
FD991551	Mobile Oil Drain Pan - 30 gallon capacity
FD991548	Alignment Kit Upgrade for 4S14C Lift

	Alignment Four-Post Lifts		General Service Four-Post Lifts	
	4A12	4A12X	4S14C	4S14CX
Capacity	12,000 LBS.	12,000 LBS.	14,000 LBS.	14,000 LBS.
Max. Wheelbase	182"	206"	180"	204"
Max. 2-Wheelbase Max. 2 Wheel Alignment	178"	202"	NA	NA
Max. 4-Wheelbase Max. 4 Wheel Alignment	125"	125"	NA	NA
Open/Closed Front	Open	Open	Closed	Closed
Lifting Height	73 $\frac{3}{4}$ "	73 $\frac{3}{4}$ "	73 $\frac{3}{4}$ "	73 $\frac{3}{4}$ "
Overall Length	20' 9"	22' 9"	20' 6"	22' 6"
Overall Width	11" 5 $\frac{5}{16}$ "	11" 5 $\frac{5}{16}$ "	11" 5 $\frac{1}{4}$ "	11" 5 $\frac{1}{4}$ "
Width Inside Columns	114 $\frac{1}{4}$ "	114 $\frac{1}{4}$ "	114 $\frac{1}{4}$ "	114 $\frac{1}{4}$ "
Length Between Columns	195"	219"	189 $\frac{1}{4}$ "	189 $\frac{1}{4}$ "
Column Height	7' 7 $\frac{1}{8}$ "	7' 7 $\frac{1}{8}$ "	7' 4"	7' 4"
Runway Height	7"	7"	7"	7"
Runway Width	20"	20"	20"	20"
Width Between Runway	43"	43"	43"	43"
Rise Time	55 sec.	55 sec.	65 sec.	65 sec.
Electrical Requirements	208V-230V	208V-230V	208V-230V	208V-230V
Minimum Bay Size	15' x 25'	15' x 27'	15' x 25'	15' x 27'



to order call 1-800-551-2228

Motorcycle Lift MC1000

1,000 lb Capacity

Motorcycle Lift 1000MCL

Length	93"
Width	48"
Full Rise	33"
Fully Lowered	7 1/4"
Weight Capacity	1,000 LBS.
Shipping Weight	600 LBS.
Portable	Yes
Air Requirement	90 psi



Accu Offers a Complete Line of Wheel Service Equipment



LOCALLY DISTRIBUTED BY



Accu Industries, Inc.

Headquarters:
P.O. Box 15540
Richmond, VA 23227
11126 Air Park Road
Ashland, VA 23005
804-798-8922
Fax 804-798-6742
www.accu-turn.com

Export Department:
Hockman-Lewis Limited
200 Executive Dr.
West Orange, NJ 07052
973-325-3838
Fax 973-325-7974
www.hl-ltd.com